Amdt. dated September 13, 2005

Reply to Office Action of June 16, 2005

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

and

1. (Currently Amended) A feed apparatus for use in depositing a slurry upon a moving web having a direction of travel, comprising:

a main metering roll;

a companion roll disposed in closely spaced relation to said metering roll to form a nip therebetween;

said nip constructed and arranged to retain a supply of the slurry;

a reciprocating slurry delivery mechanism constructed and arranged for providing slurry to said nip; and

means for driving said rolls so that slurry retained in said nip progresses in the direction of travel of said web over an upper outer peripheral surface of said metering roll to be deposited upon the web.

2. (Original) The apparatus of claim 1 further including at least one sidewall disposed closely adjacent respective ends of said rolls for forming a slurry reservoir above said nip.

Amdt. dated September 13, 2005

Reply to Office Action of June 16, 2005

3. (Original) The apparatus of claim 2 wherein said sidewalls are made of a non-stick material.

4. (Original) The apparatus of claim 1 wherein said metering roll has a relatively larger diameter than said companion roll.

5. (Original) The apparatus of claim 1 wherein said metering roll and said companion roll have one of a stainless steel peripheral surface and a resilient, non-stick peripheral surface.

6. (Original) The apparatus of claim 1 further including a thickness control roll disposed in close operational proximity to said metering roll for controlling the thickness of the slurry layer deposited upon the web by said apparatus.

- 7. (Original) The apparatus of claim 6 wherein said thickness control roll is located above said metering roll.
- 8. (Original) The apparatus of claim 6 wherein said metering roll and said companion roll rotate in the same direction and further wherein said thickness control roll rotates in the same direction as said metering and companion rolls.

Amdt. dated September 13, 2005

Reply to Office Action of June 16, 2005

9. (Original) The apparatus of claim 6 wherein said thickness control roll has a diameter substantially smaller than said metering roll.

10. (Canceled)

- 11. (Currently Amended) The apparatus of claim 101 wherein said delivery mechanism includes a conduit carrying connected to a source of slurry and having an end in close proximity to said nip, said conduit end being engaged in a reciprocating mechanism which laterally reciprocates said conduit end between ends of said metering and companion rolls.
- 12. (Original) The apparatus of claim 11 wherein said reciprocating mechanism includes a fluid powered cylinder and a cable-pulley.
- 13. (Original) The apparatus of claim 1 further including a stripping wire disposed adjacent a lower portion of said metering roll for preventing slurry from progressing upon an underside of said metering roll towards said nip.
- 14. (Original) The apparatus of claim 1 wherein said rolls are disposed generally transversely to the direction of travel of the web.

Amdt. dated September 13, 2005

Reply to Office Action of June 16, 2005

15. (Original) A feed apparatus for use in depositing a slurry upon a moving web having a direction of travel, comprising:

a main metering roll;

a companion roll disposed in closely spaced relation to said metering roll to form a nip therebetween, said rolls being disposed generally transversely to the direction of travel of the web;

said nip constructed and arranged to retain a supply of the slurry;

a thickness control roll disposed in operational relationship to said metering roll for controlling thickness of a layer of slurry drawn from said nip upon an outer surface of said metering roll; and

means for driving said metering roll, said companion roll and said thickness control roll in the same direction.

- 16. (Original) The apparatus of claim 15 wherein said direction of rotation is towards the direction of travel of the moving web.
- 17. (Original) The apparatus of claim 15 further including at least one sidewall disposed closely adjacent respective ends of said rolls for forming a slurry reservoir above said nip.

Amdt. dated September 13, 2005

Reply to Office Action of June 16, 2005

18. (Original) The apparatus of claim 15 wherein said metering roll has a larger diameter than said companion roll, and said companion roll has a larger diameter than said thickness control roll.

19. (Original) The apparatus of claim 15 further including a stripping wire disposed adjacent a lower portion of said metering roll for preventing slurry from progressing upon an underside of said metering roll towards said nip.

20. (Original) A feed apparatus for use in depositing a slurry upon a moving web having a direction of travel, comprising:

a main metering roll;

a companion roll disposed in closely spaced relation to said metering roll to form a nip therebetween, said rolls being disposed generally transversely to the direction of travel of the web;

said nip constructed and arranged to retain a supply of the slurry;

a pair of sidewalls located adjacent ends of said metering and companion rolls to form a slurry reservoir;

a thickness control roll disposed in operational relationship to said metering roll for controlling thickness of a layer of slurry drawn from said nip upon an outer surface of said metering roll;

Amdt. dated September 13, 2005

Reply to Office Action of June 16, 2005

means for driving said rolls in the same direction so that slurry retained in said nip progresses over an upper outer peripheral surface of said metering roll to be deposited upon the web; and

a reciprocating slurry delivery mechanism for providing slurry to said reservoir.